

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**PCT**WORLD INTELLECTUAL PROPERTY  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER 1

WO 9608672A1

(51) International Patent Classification 6 : <b>F17D 1/05</b>		<b>A1</b>	(11) International Publication Number: <b>WO 96/08672</b>
			(43) International Publication Date: 21 March 1996 (21.03.96)
(21) International Application Number: <b>PCT/US95/11065</b>		(81) Designated States: AU, CA, CN, FI, KZ, NO, RU, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 31 August 1995 (31.08.95)			
(30) Priority Data: 08/306,336 15 September 1994 (15.09.94) US 08/449,151 24 May 1995 (24.05.95) US		Published With international search report.	
(71) Applicant: EXXON PRODUCTION RESEARCH COMPANY [US/US]; 3120 Buffalo Speedway, P.O. Box 2189, Houston, TX 77252-2189 (US).			
(72) Inventors: COLLE, Karia, Schall; 2319 Sycamore Grove Drive, Houston, TX 77062 (US). COSTELLO, Chris- tine, Ann; 1805 Willow Drive, Easton, PA 18040 (US). OELFKE, Russell, Harlan; 18215 Spruce Creek Drive, Houston, TX 77084 (US). TALLEY, Larry, Dalton; 411 Chappel Hill Drive, Friendswood, TX 77546 (US). LONGO, John, Michael; 13819 Taylortrest Road, Houston, TX 77079 (US). BERLUCHE, Enoche; 55 Peddlers Lane, Phillipsburg, NJ 08865 (US).			
(74) Agents: CASAMASSIMA, Salvatore, J. et al.; Exxon Produc- tion Research Company, 3120 Buffalo Speedway, P.O. Box 2189, Houston, TX 77252-2189 (US).			

(54) Title: A METHOD FOR INHIBITING HYDRATE FORMATION

## (57) Abstract

A method for inhibiting the formation of clathrate hydrates in a fluid (e.g. natural gas) having hydrate-forming constituents is disclosed. The hydrate inhibitors used in the method are substantially water soluble polymers formed from an N-substituted acrylamide having two nitrogen substituent groups, R1 and R2, where R1 is a hydrocarbon group having from one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and combinations thereof, and R2 is a hydrogen atom or a hydrocarbon group having from one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of carbon, nitrogen, oxygen, and sulfur. Alternatively, R1 and R2 may be linked to produce a cyclic ring having ten atoms comprising a combination of between three and ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and combinations thereof. Some examples of such inhibitors include poly(N-ethylacrylamide), poly(N,N-diethylacrylamide), poly(N-methyl, N-acrylamide), poly(isopropylacrylamide), poly(N-propylacrylamide), poly(N-cyclopentylacrylamide), poly(N-cyclohexylacrylamide), poly(acryloylpyrrolidine), poly(acryloylpiperidine), poly(acryloylmorpholine) and various N-substituted acrylamide copolymers.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

A METHOD FOR INHIBITING HYDRATE FORMATION

This application is a continuation-in-part application of co-pending application serial number 08/306,336 filed on September 15, 1994.

FIELD OF THE INVENTION

5 The present invention relates to a method for inhibiting the formation of clathrate hydrates in a fluid. More specifically, the invention relates to a method for inhibiting the formation of gas hydrates in a pipe used to convey oil or  
10 gas.

BACKGROUND OF THE INVENTION

Carbon dioxide, hydrogen sulfide, and various hydrocarbons, such as methane, ethane, propane, normal butane and isobutane, are present in natural gas and other petroleum  
15 fluids. However, water is typically found mixed in varying amounts with such petroleum fluid constituents. Under conditions of elevated pressure and reduced temperature clathrate hydrates can form when such petroleum fluid constituents or other hydrate formers are mixed with water.  
20 Clathrate hydrates are water crystals which form a cage-like structure around guest molecules such as hydrate forming hydrocarbons or gases. Some hydrate forming hydrocarbons include, but are not limited to, methane, ethane, propane, isobutane, butane, neopentane, ethylene, propylene,  
25 isobutylene, cyclopropane, cyclobutane, cyclopentane, cyclohexane, and benzene. Some hydrate forming gases include, but are not limited to, oxygen, nitrogen, hydrogen sulfide, carbon dioxide, sulfur dioxide, and chlorine.

Gas hydrate crystals or gas hydrates are a class of  
30 clathrate hydrates of particular interest to the petroleum

industry because of the pipeline blockages that they can produce during the production and/or transport of the natural gas and other petroleum fluids. For example, at a pressure of about 1MPa ethane can form gas hydrates at temperatures below  
5 4 °C, and at a pressure of 3MPa ethane can form gas hydrates at temperatures below 14 °C. Such temperatures and pressures are not uncommon for many operating environments where natural gas and other petroleum fluids are produced and transported.

As gas hydrates agglomerate they can produce hydrate  
10 blockages in the pipe or conduit used to produce and/or transport natural gas or other petroleum fluid. The formation of such hydrate blockages can lead to a shutdown in production and thus substantial financial losses. Furthermore, restarting a shutdown facility, particularly an offshore  
15 production or transport facility, can be difficult because significant amounts of time, energy, and materials, as well as various engineering adjustments, are often required to safely remove the hydrate blockage.

A variety of measures have been used by the oil and gas  
20 industry to prevent the formation of hydrate blockages in oil or gas streams. Such measures include maintaining the temperature and/or pressure outside hydrate formation conditions and introducing an antifreeze such as methanol, ethanol, propanol, or ethylene glycol. From an engineering  
25 standpoint, maintaining temperature and/or pressure outside hydrate formation conditions requires design and equipment modifications, such as insulated or jacketed piping. Such modifications are costly to implement and maintain. The amount of antifreeze required to prevent hydrate blockages is  
30 typically between 10% to 20% by weight of the water present in the oil or gas stream. Consequently, several thousand gallons

-3-


per day of such solvents can be required. Such quantities present handling, storage, recovery, and potential toxicity issues to deal with. Moreover, these solvents are difficult to completely recover from the production or transportation stream.

Consequently, there is a need for a gas hydrate inhibitor that can be conveniently mixed at low concentrations in the produced or transported petroleum fluids. Such an inhibitor should reduce the rate of nucleation, growth, and/or agglomeration of gas hydrate crystals in a petroleum fluid stream and thereby inhibit the formation of a hydrate blockage in the pipe conveying the petroleum fluid stream.

One method of practicing the present invention uses gas hydrate inhibitors which can be used in the concentration range of about 0.01% to about 5% by weight of the water present in the oil or gas stream. As discussed more fully below, the inhibitors of this invention can effectively treat a petroleum fluid having a water phase.

#### SUMMARY OF THE INVENTION

According to the invention there is provided a method for inhibiting the formation of clathrate hydrates in a fluid having hydrate forming constituents. The method comprises treating said fluid with an inhibitor comprising a substantially water soluble polymer produced from the following N-substituted acrylamide:



where,

$R_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof,


$R_2$  is hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, and,

$x$  is an average number of repeating monomeric units for producing an average molecular weight for said polymer between about 1,000 and about 6,000,000 for said polymer.

Preferably the method is practiced wherein  $R_1$  is an alkyl, cycloalkyl, aryl, alkaryl, or aralkyl group having said zero to four heteroatoms and  $R_2$  is a hydrogen atom or an alkyl, cycloalkyl, aryl, alkaryl, or aralkyl group having said zero to four heteroatoms. However, the method may also be practiced wherein  $R_1$  is an alkoxyalkyl, alkenyl, or alkynyl group having said zero to four heteroatoms and  $R_2$  is an alkoxyalkyl, alkenyl, or alkynyl group having said zero to four heteroatoms. Also, the method may be practiced wherein  $R_1$  and  $R_2$  are linked to produce a cyclic moiety having between three and ten carbon atoms and said zero to four heteroatoms.

One embodiment of the invention includes treating the fluid with an inhibitor mixture having, (a) an inhibitor comprising a substantially water soluble polymer produced from the following N-substituted acrylamide:

-5-



where,

$\text{R}_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof,

$\text{R}_2$  is hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, and,

$x$  is an average number of repeating monomeric units for producing an average molecular weight for said polymer between about 1,000 and about 6,000,000 for said polymer, and;

b) a liquid for introducing said inhibitor into said fluid. Preferably, such liquid is an alcohol, water, brine, or some mixture thereof.

Some preferred inhibitors which can be used to practice the invention include, but are not limited to, substantially water soluble polymers that can be produced from a N-substituted acrylamide selected from the group consisting of poly(N-ethylacrylamide), poly(N,N-diethylacrylamide), poly(N-methyl, N-ethylacrylamide), poly(N-cyclopentylacrylamide), poly(N-cyclohexylacrylamide), poly(acryloylpyrrolidine), poly(acryloylpiperidine), poly(acryloylmorpholine) and N-substituted acrylamide copolymers. Furthermore, the nitrogen substituents for such water soluble polymers can be selected



from the group consisting of a hydrogen, alkyl, and cycloalkyl groups.

### DETAILED DESCRIPTION OF THE INVENTION

#### INVENTIVE METHOD

5       The inventive method inhibits the formation of clathrate hydrates in a fluid having hydrate forming constituents. Formation of clathrate hydrates means the nucleation, growth, and/or agglomeration of clathrate hydrates. Such clathrate hydrates may be formed in a fluid whether it is flowing or  
10 substantially stationary, but are often most problematic in flowing fluid streams conveyed in a pipe. For example, flow restrictions arising from partial or complete blockages in a fluid stream can arise as clathrate hydrates adhere to and accumulate along the inside wall of the pipe used to convey  
15 the fluid. Nonetheless, the invention can be used for inhibiting formation of clathrate hydrates in substantially stationary fluids.

In one embodiment of the invention, a concentrated solution or mixture of one or more of the inhibitors of the  
20 type described below is introduced into a petroleum fluid stream having an aqueous phase. As the inhibitor solution or mixture of this invention is substantially dissolved in the aqueous phase or dispersed in the fluid stream it reduces the rate that clathrate hydrates are formed, and thereby reduces  
25 the tendency for a flow restriction to occur.

In a preferred embodiment, the solid polymer is first dissolved into an appropriate carrier solvent or liquid to make a concentrated solution or mixture. It should be understood that many liquids may effectively facilitate  
30 treatment of the fluid stream without dissolving the inhibitor. Many liquids, however, will preferably dissolve

-7-

the inhibitor and, for convenience, are referred to hereafter as solvents whether they produce an inhibitor solution, emulsion, or other type of mixture. The solvent's principal purpose is to act as a carrier for the inhibitor and to  
5 facilitate the inhibitor's absorption into the aqueous phase of the petroleum fluid. Any solvent suitable for delivering the inhibitor to the fluid's aqueous phase may be used. Such solvents include, but are not limited to, water, brine, sea water, produced water, methanol, ethanol, propanol,  
10 isopropanol, glycol, or mixtures of such solvents. Other solvents familiar to those skilled in the art may also be used.

It should be understood that the use of a carrier solvent is not required to practice the invention, but it is a  
15 convenient method of introducing the inhibitor into the fluid. In many applications the use of a carrier solvent will facilitate treatment of the fluid stream.

Any convenient concentration of inhibitor in the carrier solvent can be used, so long as it results in the desired  
20 final concentration in the aqueous phase of the petroleum fluid. Higher concentrations are preferred, since they result in a reduced volume of concentrated solution to handle and introduce into the petroleum fluid. The actual concentration used in a specific application will vary depending upon the  
25 selection of carrier solvent the chemical composition of the inhibitor, the system temperature, and the inhibitor's solubility in the carrier solvent at application conditions.

The inhibitor mixture is introduced into the aqueous phase of the petroleum fluid using mechanical equipment, such  
30 as, chemical injection pumps, piping tees, injection fittings, and other devices which will be apparent to those skilled in

the art. However, such equipment is not essential to practicing the invention. To ensure an efficient and effective treatment of the petroleum fluid with the inhibitor mixture two points should be considered.

5 First an aqueous phase is preferably present at the location the inhibitor solution is introduced into the fluid. In some petroleum fluid systems (particularly natural gas systems), an aqueous phase does not appear until the gas has cooled sufficiently for water to condense. If this is the  
10 case, the inhibitor solution is preferably introduced after the water has condensed. Alternatively, in the event that an aqueous phase is not available at the point the inhibitor solution is introduced, the inhibitor solution concentration should be selected to ensure that the inhibitor solution's  
15 viscosity is sufficiently low to facilitate its dispersion through the fluid and permit it to reach the aqueous phase.


Second, because the inhibitor primarily serves to inhibit the formation of clathrate hydrates, rather than reverse such formation, it is important to treat the fluid prior to  
20 substantial formation of clathrate hydrates. As a wet petroleum fluid cools it will eventually reach a temperature, known as the hydrate equilibrium dissociation temperature or  $T_{eq}$ , below which hydrate formation is thermodynamically favored. A petroleum fluid's  $T_{eq}$  will shift as the pressure  
25 applied to the fluid and the its composition change. Various methods of determining a fluid's  $T_{eq}$  at various fluid compositions and pressures are well known to those skilled in the art. Preferably, the fluid should be treated with the inhibitor when the fluid is at a temperature greater than its  
30  $T_{eq}$ . It is possible, but not preferable, to introduce the inhibitor while the temperature is at or slightly below the

fluid's  $T_{eq}$ , preferably before clathrate hydrates have begun to form.

The quantity of inhibitor introduced into a petroleum fluid with an aqueous phase solvent will typically vary  
5 between about 0.01 wt% to about 5 wt% by weight of the water present in the fluid. Preferably, the inhibitor concentration will be about 0.5 wt%. For example, a laboratory study has shown that adding 0.5 wt% of poly(N,N-diethylacrylamide) to a petroleum fluid allowed the fluid to cool to a temperature  
10 which was about 12 °C below its  $T_{eq}$  without formation of a hydrate blockage. A higher inhibitor concentration can be used to lower the temperature at which a hydrate blockage is obtained. A suitable concentration for a particular application, however, can be determined by those skilled in  
15 the art by taking into account the inhibitor's performance under such application, the degree of inhibition required for the petroleum fluid, and the inhibitor's cost.

#### INHIBITOR DESCRIPTION


Compounds belonging to the group of polymers and  
20 copolymers of acrylamides, and mixtures thereof, are very effective inhibitors of hydrate nucleation, growth, and/or agglomeration (collectively referred to as hydrate formation). A generic structure of the acrylamide homopolymers is depicted as follows:



where  $R_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof and  $R_2$  is a hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, such that the resultant polymer is substantially water soluble, and  $x$  is an average number sufficient to produce an average molecular weight between 1,000 to about 6,000,000.

It is well understood by those skilled in the art that a given polymer composition is comprised of polymers having variable chain lengths and molecular weights, with some above and some below the polymer's average molecular weight. Therefore, some polymer chains contain less than  $x$  repeating units, and some polymer chains contain more than  $x$  repeating units. Accordingly,  $x$  represents an average number of repeating units over the distribution of polymer chains comprising a given polymer composition.


$R_1$  and  $R_2$  may also be linked to produce a cyclic structure containing the nitrogen atom linking  $R_1$  and  $R_2$ . The generic form of such a structure is shown below where  $X$  and  $Y$  have been substituted for  $R_1$  and  $R_2$ .




The cyclic structure produced by the X-Y linkage may contain up to 10 atoms, with 3 to 10 carbon atoms and zero to four

heteroatoms, including but not limited to, nitrogen, oxygen, and/or sulfur.

N-substituted acrylamide copolymers are also effective inhibitors of hydrate nucleation, growth, and/or agglomeration. A generic structure of such copolymers is depicted as follows:



In such copolymers, the first monomer may have  $\text{R}_1$  and  $\text{R}_2$  in any combination of hydrogen, methyl, and ethyl groups provided  $\text{R}_1$  and  $\text{R}_2$  are not both hydrogen and the second monomer will have  $\text{R}_3$  = hydrogen, while  $\text{R}_4$  may be  $\text{C}_3$ - $\text{C}_{10}$  alkyl group (branch, normal, or cyclic) with zero to four heteroatoms such that the resultant copolymer is substantially water soluble. Also, an acrylamide copolymer may be produced from an acrylamide monomer with a nitrogen containing cyclic group pendant to the carbonyl moiety. Generically, such a copolymer can be illustrated as follows.



In mixed copolymers comprising an acrylamide monomer linked with another monomer type, the acrylamide monomer must not exceed a total of ten carbon atoms between  $\text{R}_1$  and  $\text{R}_2$ .  $\text{R}_1$

may be hydrogen or an alkyl group (normal, branched, or cyclic) having from one to ten carbon atoms and zero to four heteroatoms and R<sub>2</sub> may be an alkyl group (normal, branched, or cyclic) having from one to ten carbon atoms. Alternatively, the first and second nitrogen substituents of the acrylamide may be linked to form a nitrogen containing cyclic structure with three to ten carbon atoms and zero to four heteroatoms, including but not limited to, nitrogen, oxygen and/or sulfur. The other monomer in such mixed copolymers may be chosen from a class of monomers including, but not limited to, other N-substituted acrylamides, vinylpyrrolidone, vinylcaprolactam, acrylates and vinyl carboxylates, such that the resultant copolymer is substantially water soluble. For example, vinylpyrrolidone could be copolymerized with N-butyl acrylamide to produce an effective inhibitor in the class of the mixed copolymers described above. Other monomers that could be copolymerized with N-substituted acrylamide monomers to produce a mixed copolymer inhibitor include Zwitterionic moieties such as N-(3-sulfopropyl)-N-methacryloylamidopropyl-N,N-dimethylammonium betaine (SPP).


These various acrylamide polymers and copolymers may be used in mixture with other substantially water soluble polymers, including but not limited to, polyvinylpyrrolidone (PVP), polyvinylcaprolactam (PVCap), or copolymers of PVP or PVCap.

Without limiting the scope of the invention, and for the purpose of illustrating the invention, various polymeric acrylamide inhibitors were evaluated including polyacrylamide, poly(N-methylacrylamide), poly(N-ethylacrylamide), poly(N,N-dimethylacrylamide), poly(N,N-diethylacrylamide) poly(acryloylpyrrolidine), poly(acryloylpiperdine),


-13-

poly(acryloylmorpholine). These structures are depicted below.


PAM = Polyacrylamide ( $R_1=R_2=H$ )




5 PMAM = Poly(N-methylacrylamide) ( $R_1 = H, R_2 = \text{CH}_3$ )



PEAM = Poly(N-ethylacrylamide) ( $R_1 = H, R_2 = \text{C}_2\text{H}_5$ )




PDMAM = Poly(N,N-dimethylacrylamide) ( $R_1=R_2=\text{CH}_3$ )







PDEAM = Poly(N,N-diethylacrylamide) ( $R_1=R_2=C_2H_5$ )




PAPYD = Poly(acryloylpyrrolidine)



5 PAPID = Poly(acryloylpiperidine)




PAMPHL = Poly(acryloylmorpholine)




One copolymer comprising a 50:50 monomer ratio of N-n-propylacrylamide and vinylpyrrolidone was prepared for evaluation. The structure for this copolymer is provided below.

5 VP/NnPAM = Copolymer of Vinylpyrrolidone and  
N-n-propylacrylamide




Two examples of a polyacrylamide with a cyclic substituent that are expected to be effective inhibitors, but not yet evaluated, are poly(N-cyclopentylacrylamide), poly(N-cyclohexylacrylamide) and a copolymer of acryloylhexamethyleneimine and vinyl pyrrolidone, depicted below.


10 PCPAM = Poly(N-cyclopentylacrylamide) ( $R_1 = \text{cycloC}_5\text{H}_9$  and  $R_2 =$   
15 H)



PCHAM = Poly(N-cyclohexylacrylamide) ( $R_1=C_6H_{11}$  and  $R_2=H$ )



VP/AHMI = Copolymer of Acryloylhexamethyleneimine and Vinyl Pyrrolidone



5

### INHIBITOR SYNTHESIS

#### General Procedure

Many of these acrylamide polymers and copolymers, their monomers, and lactam polymers such as polyvinylpyrrolidone, and polyvinylcaprolactam are commercially available through chemical manufacturers. Other members of the acrylamide polymer class and monomers that are not commercially available may be readily synthesized by procedures known to those skilled in the art. References for representative polymer synthesis procedures may be found in S.R. Sandler and W. Karo, *Polymer Syntheses*, Vol. 1 (2nd Edition), Academic Press: New York, 1992, Chapter 12. Monomers which were not commercially available were synthesized from the appropriate amine and acryloyl chloride, using either benzene or diethyl ether as

solvents, according to published procedures (see, e.g., S. Ito, *Kobunshi Ronbunshu*, 46(7), pp. 437-443, July 1989).

Where polymer synthesis was required, water was used as a solvent and ammonium persulfate was used as an initiator when the polymer was water soluble at the polymerization temperature. However, for polymers not soluble at the polymerization temperature, because they exhibit a lower critical solution temperature (LCST) in water, either benzene or methanol was used as a solvent and 2,2' azobis(2-methylpropionitrile) ("AIBN") was used as an initiator. For convenience, however, synthesis procedures for PDMAM and PDEAM are provided below.

Polymerization of N,N-dimethylacrylamide (DMAM)

DMAM was purified by fractional distillation at 80 °C and 13 torr. The DMAM was stored in the dark under nitrogen at 4 °C prior to use. Deionized water was degassed by bringing the water to a rapid boil while purging it with a strong argon purge for about 90 minutes. The purging continues until the deionized water cools to room temperature.

A 300 ml resin flask was equipped with a mechanical stirrer, condenser, thermometer, and an argon inlet/outlet. The flask was purged with argon for about 30 minutes. 193 ml of the degassed water was transferred to the resin flask under argon, then 19.24 g (194.1 mmol) of DMAM was transferred via cannula and dissolved with stirring. The reaction solution was brought to 60 °C while stirring and purging with argon, at which point an ammonium persulfate solution (0.044g in 5 ml of deionized, degassed water) was transferred via cannula to the flask. After about five minutes of reaction time, polymerization was evident by a temperature rise to about 64 °C and an increase in the viscosity of the reaction mixture.

Because of the reaction mixture's high viscosity, it was maintained at 60 °C overnight under argon but without stirring.

The following day the viscous polymer solution was removed from the flask and placed in a freeze-drier. The  
5 water was removed in accordance with the directions on the freeze-drier over about a 48 hour period. The reaction yields about 89% crude polymer product. The dried product was subsequently dissolved in methanol, precipitated with diethyl ether and dried in a vacuum oven at 50 °C and  $10^{-3}$  torr. The  
10 structure of the polymer product, poly(N,N-dimethylacrylamide), was confirmed using carbon-13 and proton nuclear magnetic resonance (NMR) spectroscopy.

Polymerization of N,N-diethylacrylamide (DEAM)

DEAM was purified by vacuum distillation at 76 °C and 7  
15 torr. The DEAM was stored in the dark under nitrogen at 4 °C prior to use. Deionized water was degassed by bringing the water to a rapid boil while purging it with a strong argon purge for about 90 minutes. The purging continues until the deionized water cools to room temperature.

20 A 300 ml resin flask was equipped with a mechanical stirrer, condenser, thermometer, and an argon inlet/outlet. The flask was purged with argon for about 30 minutes. 193 ml of the degassed water was transferred to the resin flask under argon, then 9.2 g (72.5 mmol) of DMAM was transferred via  
25 cannula and dissolved with stirring. The reaction solution was brought to 30 °C while stirring and purging with argon, at which point an ammonium persulfate solution (0.022g in 5 ml of deionized, degassed water) was transferred via cannula to the flask. After about two hours and no sign of reaction, an  
30 additional aliquot of ammonium persulfate solution (0.040 g in 5 ml of deionized, degassed water) was introduced to the

-19-

reaction mixture. The reaction mixture was maintained at 30 °C while stirring overnight.

The following day the reaction mixture has a milky appearance but clears upon cooling to room temperature. The  
5 polymer solution was removed from the flask and placed in a freeze-drier. The water was removed in accordance with the directions on the freeze-drier over about a 48 hour period. The reaction yields about 93% crude polymer product. The dried product was subsequently dissolved in tetrahydrofuran  
10 (THF), precipitated with hexane and dried in a vacuum oven at 60 °C and  $10^{-3}$  torr. The structure of the polymer product, poly(N,N-diethylacrylamide), was confirmed using proton NMR spectroscopy.

Polymerization of Vinylpyrrolidone (VP) and N-n-propylacrylamide (NnPAM)  
15

N-n-propylacrylamide (NnPAM) and vinylpyrrolidone were purchased from a commercial vendor and used as received. Anhydrous methanol was degassed by vigorously bubbling dry nitrogen through it.

20 A 250 mL flask equipped with a mechanical stirrer, condenser, thermometer, and a nitrogen inlet was purged with nitrogen. The flask was charged with NnPAM (0.1 mole, 11.34 g) and VP (0.1 mole, 11.13 g) in about 100 mL of degassed methanol. 0.26 g AIBN (azobisisobutyronitrile) was added, and  
25 the flask was heated to 65 C for 8 hours with stirring. The reaction mixture was cooled, and the copolymer was isolated by removal of the solvent and drying overnight in a vacuum oven at 50 C. The structure of the copolymer (50:50 NnPAM:VP) was confirmed using carbon-13 NMR spectroscopy.

INHIBITOR EVALUATIONLaboratory Evaluation ProceduresTHF Testing

One method for evaluating an inhibitor's effectiveness is a bench-scale atmospheric pressure test often referred to as a tetrahydrofuran or THF test. A THF test typically uses 3mL of tetrahydrofuran (THF) and 9 mL of ASTM synthetic seawater (SSW) containing the desired amount of inhibitor additive. The THF and SSW are placed in a capped test tube (15 mm OD x 12.5 cm long) with a 0.95 centimeter stainless steel ball. Each tube is placed in a ferriswheel-type holder and placed in a cooling bath held near 0 °C. The tubes are rotated to facilitate mixing of the samples. The tubes are monitored visually and recorded with a video camera. As hydrate formation proceeds the viscosity of THF/SSW solution increases. In many instances the solution's viscosity will become high enough for the ball to stop moving. The time required for the stainless steel ball to stop moving the full length of the tube is referred to as ball stop time or BST.

The BST is an approximate indication of an inhibitor's effectiveness. Because the THF/SSW solution has a  $T_{eq}$  of about 2-5 °C and THF is miscible with water, hydrate formation is substantially accelerated for the THF/SSW solution as compared to petroleum fluids conveyed in a pipeline or flowline under typical field conditions. Therefore, BSTs are useful for indicating which inhibitors may be effective under field applications. A BST for a THF/SSW solution with an inhibitor which is about three times the BST for a THF/SSW control solution with no inhibitor present indicates that the inhibitor demonstrates a threshold inhibition effect. Therefore, as used herein, a threshold inhibition

-21-

concentration ("TIC") means the inhibitor concentration in a THF/SSW solution required to produce a BST which is about three times the BST for a THF/SSW control solution. Because the THF test results are sensitive to variations in the temperature at which the test is run, rotation frequency of the tube, clearances between the stainless steel ball and tube wall, etc., it is important to run a THF/SSW control solution with each inhibitor evaluation to ensure that an inhibitor's TIC is accurately measured and that a reliable threshold inhibition effect is observed.

#### Mini-loop Testing

A second method for evaluating an inhibitor's effectiveness uses a bench-scale high pressure apparatus referred to as a mini-loop apparatus. A mini-loop apparatus consists of a loop of stainless steel tubing with about a one-half inch inside diameter and about ten feet in length. The loop also has a transparent section for observing the fluid flow in the loop and the onset of hydrate formation in the loop. Fluid comprising about 40% by volume SSW solution having about 3.5% total ionized salts, 40% by volume hydrocarbon condensate (i.e.,  $C_6+$ ), and 20% by volume hydrocarbon gas mixture is circulated around the loop at constant pressure. The hydrocarbon gas mixture is comprised of about 76 mole% methane, 9 mole% ethane, 7 mole% propane, 5 mole% n-butane, 2 mole% iso-butane, and 1 mole% of  $C_5+$ . The inhibitor is typically injected into the loop as an aqueous solution to produce the desired weight percent concentration of inhibitor in the aqueous sea salt/gas solution. Generally, many hydrate inhibitors are evaluated at about 0.5 wt.% of the aqueous sea salt/gas solution.



-22-

The fluid is circulated at a constant velocity of about 2.5 feet/second. The loop and its pump lay in a controlled temperature water bath for controlling the temperature of the fluid circulating in the loop. The bath's water is circulated  
5 to ensure uniform temperature throughout the bath and rapid heat transfer between the bath water and the loop. As the loop temperature changes or as hydrates form the gas volume in the loop will change accordingly. Therefore, to maintain constant pressure in the loop a pressure compensating device  
10 is required. Such a device can be comprised of a gas cell and a hydraulic oil cell separated by a floating piston. So as the gas volume in the loop changes, oil may be added or removed from the oil cell to produce a commensurate addition or removal of gas to the loop. Mini-loop tests are typically  
15 run at a pressure of about 1,000 pounds per square inch gauge (p.s.i.g.). However, any pressure between 0 to 3,000 p.s.i.g. could be selected for evaluating an inhibitor's performance.

The temperature of the water bath is reduced at a constant rate, preferably about 6 °F per hour, from an initial  
20 temperature of about 70 °F. At some temperature, clathrate hydrates begin to rapidly form. As the dissolved gas is used to form clathrate hydrates there is an abrupt and corresponding decrease in the volume of dissolved gas in the aqueous sea salt/gas solution. The temperature at which this  
25 abrupt decrease in the volume of dissolved gas is observed is known as the temperature of onset for hydrate formation ( $T_{o_h}$ ). Recalling from the discussion above, the hydrate equilibrium dissociation temperature or  $T_{eq}$  is the temperature below which hydrate formation is thermodynamically favored in an aqueous  
30 sea salt/gas solution without an inhibitor present. Therefore, another measure of an inhibitor's effectiveness is

-23-

the difference between  $T_{eq}$  and  $T_{os}$  which is known as the inhibitor's subcooling,  $T_{sub}$ . Therefore, for a given pressure, the greater the subcooling the more effective the inhibitor. Typically, an aqueous sea salt/gas solution with no inhibitor present produces a  $T_{sub}$  of about 6-7 °F.

#### THF and Mini-loop Test Results

Without limiting the scope of the invention, and for the purpose of illustrating the invention, various polymeric acrylamide inhibitors were evaluated including PAM, PMAM, PEAM, PDMAM, PDEAM, PAPYD, PAPID, PAMPHL and VP/NnPAM. All inhibitors except PDEAM and VP/NnPAM were evaluated at 0.5 % by weight of the water present in the THF/SSW solution. PDEAM and VP/NnPAM were evaluated at 0.25 wt%. A THF/SSW solution with no inhibitor present was evaluated as a control.

-24-

TABLE 1

THF AND MINI-LOOP TEST RESULTS WITH POLYMERIC ACRYLAMIDE  
INHIBITORS

INHIBITOR	CONC., WT%	BALL STOP TIME (MINUTES)	CONC., WT%	MINI-LOOP SUBCOOLING TEMP. (°F)
None	---	6	---	7
PAM	0.5	10	--	--
PMAM	0.5	41	0.5	11.7
PEAM	0.5	>1136	0.5	15.5
PDMAM	0.5	14	0.5	11.4
PDEAM	0.25	>1400	0.5	21.5
PiPAM	0.5	13	0.5	20.0
VP/NnPAM	0.25	80	--	--
PAPYD	0.5	>1400, >3950	0.5	25.2
PAPID	0.5	28, 29	0.5	11.0
PAMPHL	0.5	13, 10	0.5	19.0

5       The results above show that certain acrylamides, such as  
PDMAM and PiPAM, do not have any THF threshold inhibition  
effect (i.e., greater than three times the BST for the  
uninhibited control), but nonetheless, do show a mini-loop  
threshold inhibition effect (i.e., a subcooling temperature at  
10 least 1.5 °F greater than the uninhibited control). For  
example, PiPAM has a 13 minute BST which is below the 18  
minute BST for demonstrating a THF threshold inhibition  
effect, but a 20 °F mini-loop subcooling which is well above  
the 8.5 °F mini-loop subcooling for demonstrating a mini-loop  
15 threshold inhibition effect.

The THF and corresponding mini-loop test results for a  
given inhibitor indicates only that an inhibitor demonstrating


-25-

a threshold inhibition effect under THF testing will also demonstrate a threshold inhibition effect under mini-loop testing. An inhibitor that fails to demonstrate a THF threshold inhibition effect under THF testing, however, may or  
5 may not demonstrate a threshold inhibition effect under mini-loop testing. Currently, there is no apparent method for quantitatively predicting an inhibitor's mini-loop performance based on its performance under THF testing. Mini-loop testing, however, more closely simulates the conditions, such  
10 as flow, pressure, and gas mixture, which are likely to be found in most field applications of the inhibitor. Consequently, mini-loop test results are a more reliable indicator than THF test results of an inhibitor's potential effectiveness under typical field applications.

15 The means and method invention and the best mode contemplated for practicing the invention have been described. It is to be understood that the foregoing is illustrative only and that other means and techniques can be employed without departing from the true scope of the invention defined in the  
20 following claims.

We claim:

1. A method for inhibiting the formation of clathrate hydrates in a fluid having hydrate forming constituents, said method comprising treating said fluid with an inhibitor
- 5 comprising a substantially water soluble polymer produced from the following N-substituted acrylamide:



where,

- 10  $\text{R}_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof,
- $\text{R}_2$  is hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected
- 15 from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, and,
- $x$  is an average number of repeating monomeric units for producing an average molecular weight for said polymer
- 20 between about 1,000 and about 6,000,000 for said polymer.
2. The method of claim 1 wherein  $\text{R}_1$  is an alkyl, cycloalkyl, aryl, alkaryl, or aralkyl group having said zero to four heteroatoms and  $\text{R}_2$  is a hydrogen atom or an alkyl, cycloalkyl, aryl, alkaryl, or aralkyl group having said zero
- 25 to four heteroatoms.

-27-

3. The method of claim 1 wherein  $R_1$  is an alkoxyalkyl, alkenyl, or alkynyl group having said zero to four heteroatoms and  $R_2$  is an alkoxyalkyl, alkenyl, or alkynyl group having said zero to four heteroatoms.

5 4. The method of claim 1 wherein  $R_1$  and  $R_2$  are linked to produce a cyclic moiety having ten atoms comprising a combination of between three and ten carbon atoms and said zero to four heteroatoms.

5. The method of claim 1 wherein said N-substituted  
10 acrylamide produces a polyalkylacrylamide selected from the group consisting of poly(N-methylacrylamide), poly(N-ethylacrylamide), poly(N,N-diethylacrylamide), poly(N-methyl, N-ethylacrylamide), poly(iso-propylacrylamide), poly(n-propyl acrylamide), poly(N-cyclopentylacrylamide), poly(N-  
15 cyclohexylacrylamide), copolymers formed from N-substituted acrylamides, and mixed copolymers formed from N-substituted acrylamides and monomers selected from the group consisting of vinylpyrrolidone, vinylcaprolactam, vinyloxazoline, acrylates, and vinyl carboxylates.


20 6. The method of claim 2 wherein said N-substituted acrylamide produces a polyalkylacrylamide selected from the group consisting of poly(acryloylpyrrolidine), poly(acryloylpiperdine), poly(acryloylmorpholine) copolymers formed from N-substituted acrylamides, and mixed copolymers  
25 formed from N-substituted acrylamides and monomers selected from the group consisting of vinylpyrrolidone, vinylcaprolactam, vinyloxazoline, acrylates, and vinyl carboxylates.

7. The method of claim 1 wherein said inhibitor further  
30 comprises a substantially water soluble polymer selected from the group consisting of polyvinylpyrrolidone, polyvinylcaprolactam, and N-acyl substituted polyalkeneimines.

8. A method for inhibiting the formation of clathrate hydrates in a fluid having hydrate forming constituents, said method comprising:

treating said fluid with an inhibitor mixture having,

- 5 a) an inhibitor comprising comprising a substantially water soluble polymer produced from the following N-substituted acrylamide:



where,

10  $\text{R}_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof,

15  $\text{R}_2$  is hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, and,

20  $x$  is an average number of repeating monomeric units for producing an average molecular weight for said polymer between about 1,000 and about 6,000,000 for said polymer, and;

25 b) a liquid used for introducing said inhibitor into said fluid.

9. The method of claim 8 wherein said N-substituted acrylamide produces a polyalkylacrylamide selected from the group consisting of poly(N-methylacrylamide), poly(N-ethylacrylamide), poly(N,N-diethylacrylamide), poly(N-methyl,  
5 N-ethylacrylamide), poly(iso-propylacrylamide), poly(n-propylacrylamide), poly(N-cyclopentylacrylamide), and poly(N-cyclohexylacrylamide), copolymers formed from N-substituted acrylamides, and mixed copolymers formed from N-substituted  
10 vinylpyrrolidone, vinylcaprolactam, vinylloxazoline, acrylates, and vinyl carboxylates.

10. The method of claim 9 wherein said nitrogen substituents are selected from the group consisting of a hydrogen, alkyl, and cycloalkyl group.

15 11. The method of claim 8 wherein said inhibitor mixture further comprises a substantially water soluble polymer selected from the group consisting of polyvinylpyrrolidone, polyvinylcaprolactam, and N-acyl substituted polyalkeneimine.


12. The method of claim 8 wherein said liquid is  
20 selected from the group consisting of an alcohol, water, and brine.

13. The method of claim 8 wherein  $R_1$  and  $R_2$  are linked to produce a cyclic moiety having ten atoms comprising a combination of between three and ten carbon atoms and said  
25 zero to four heteroatoms.

14. A method for inhibiting the formation of clathrate hydrates in a pipe containing a petroleum fluid stream having hydrate forming constituents, said method comprising:

- a) producing an inhibitor mixture having,  
30 1) an inhibitor comprising comprising a substantially water soluble polymer produced from the following N-substituted acrylamide:





where,

$\text{R}_1$  is a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, sulfur, and, combinations thereof,

$\text{R}_2$  is hydrogen atom or a hydrocarbon group having one to ten carbon atoms and zero to four heteroatoms selected from the group consisting of nitrogen, oxygen, and sulfur, and combinations thereof, and,

$x$  is an average number of repeating monomeric units for producing an average molecular weight for said polymer between about 1,000 and about 6,000,000 for said polymer, and;

2) a liquid used for introducing said inhibitor into said fluid; and

b) introducing said inhibitor mixture into said petroleum fluid stream, thereby inhibiting the formation of a hydrate restriction in said pipe.

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/11065

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :F17D 1/05

US CL :585/15, 950; 137/3, 13; 166/310, 371

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 585/15, 950; 137/3, 13; 166/310, 371

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS-search terms: hydrate, 7acrylamide, polymer7, clathrate

STN-CA-search terms: hydrate, 7acrylamide, polymer7, clathrate

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 4,856,593 (MATTHEWS ET AL.) 15 August 1989, col. 1, line 66 through col. 2, line 8 and col. 5, lines 38-65.	1-14
Y	WO, A, 93/25798 (ANSELME ET AL.) 23 December 1993, page 3, line 11 through page 4, line 3.	5-7, 9-11, 13
A	US, A, 4,973,775 (SUGIER ET AL.) 27 November 1990.	1-14
A	US, A, 5,076,373 (HALE ET AL.) 31 December 1991.	1-14
P,A	US, A, 5,420,370 (SLOAN, JR.) 30 May 1995.	1-14

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

\* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\*

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\*

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\*

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

\*A\*

document member of the same patent family

Date of the actual completion of the international search

26 SEPTEMBER 1995

Date of mailing of the international search report

12 DEC 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231Authorized official  
WALTER GRIFFIN

Facsimile No. (703) 305-3230

Telephone No. (703) 308-0661